NEWAY®

P2150 / P2150S

21.5" Professional Video Monitor

1920×1080 | 3G-SDI 4K-HDMI | 1000 nit | HDR

High brightness Monitor with FHD Resolution, 101% Rec.709 color space,
Application for live events, conference presentation, public view monitoring, etc.

Layout and Composition

The image output from the camera to TV live is often slashed. This monitor comes with Center Markers and Safety Markers, allowing to adjust the best angle of cameras in real time to show the most important images in center of shot.

Audio Level Monitoring

With Audio Level Meter turned on, it is used to monitor current audio output and avoid being indifferent after an audio interruption as well as keep the sound within a reasonable DB range.

Public View

Education

Concert

Live Stream

E-Sport

Wedding

1000 nit High-Bright

Featuring an amazing 1000 nit High Bright LCD screen, with the sunshine readable screen which cover 101% Rec.709 color space, therefore the gear suitable for any innovative outdoor framing.

HDR

When HDR is activated, the display reproduces a greater dynamic range of luminosity, allowing lighter and darker details to be displayed more clearly. Effectively enhancing the overall picture quality.

Wall-mount

It can be installed and fixed on the wall through the VESA 75/100 mm screw points at its back.

SPECIFICATIONS

		P2150S	P2150
DISPLAY	Panel	21.5" LCD	21.5" LCD
	Physical Resolution	1920×1080	1920×1080
	Aspect Ratio	16:9	16:9
	Brightness	1000 cd/m²	1000 cd/m²
	Contrast	1500:1	1500:1
	Viewing Angle	170°/ 170°(H/V)	170°/ 170°(H/V)
	Color Space	101% Rec.709	101% Rec.709
	HDR Supported	HLG, ST2084 300/1000/10000	HLG, ST2084 300/1000/10000
INPUT	SDI	1 × 3G-SDI	-
	HDMI	1 × HDMI 1.4b	1 × HDMI 1.4b
	VGA	1	1
	AV	1	1
OUTPUT	SDI	1 × 3G-SDI	-
SUPPORTED FORMATS	SDI	1080p 24/25/30/50/60, 1080i 50/60, 720p 50/60	-
	HDMI	2160p 24/25/30, 1080p 24/25/30/50 /60, 1080i 50/60, 720p 50/60...	2160p 24/25/30, 1080p 24/25/30/50 /60, 1080i 50/60, 720p 50/60...
AUDIO IN/OUT	Speaker	2	2
	SDI	16ch 48kHz 24-bit	-
	HDMI	8ch 24-bit	8ch 24-bit
	Ear Jack	3.5mm - 2ch 48kHz 24-bit	3.5mm - 2ch 48kHz 24-bit
POWER	Input Voltage	DC 12-24V	DC 12-24V
	Power Consumption	≤36W (15V)	≤36W (15V)
ENVIRONMENT	Operating Temperature	0°C~50°C	0°C~50°C
	Storage Temperature	-20°C~60°C	-20°C~60°C
DIMENSION	Dimension(L/W/D)	524.8mm × 313.3mm × 19.8mm	524.8mm × 313.3mm × 19.8mm
	Weight	4.8kg	4.8kg

Note: Due to constant effort to improve products and product features, specifications may change without notice.

ACCESSORIES

STANDARD

15V 4A DC Power Adapter

HDMI A to A Cable

VGA Cable

Audio & Video Input Cable

Base Stand

User Manual

www.newayhd.com

Quanzhou NEWAY Industrial Limited
Tel: +86-595-22519926 / Fax: +86-595-22519925
Email: info@neway.me